

TEVO-VHD4K comes with an Ultra-HD imaging system, Rally delivers brilliantly sharp video, outstanding color, and exceptional optical accuracy at resolutions up to 4K. This camera adopts 1/2.5"CMOS (SONY IMX274) , 8.29 effective mage pixel, 138 °super-wide field of view, to emphasize faces and render natural-looking skin tones, even in dim or backlit conditions. VHD4K meets with the application for Ultra HD recording and streaming, video conferencing, and broadcasting that supports USB cameras.

Key Features

Automatic camera control

1/2.5"CMOS Sensor (SONY IMX274)

4k(3840X2160)Ultra HD video resolution

Preset: 9 via IR remote setting (255 via RS232)

Equipped with IR remote control, easy to operate

High precise motor positioning (Pan:340°,Tilt: 120°)

UVC/plug-and-play at MJPEG via USB, 4K@30FPS

Support ceiling mount, wall mount and tripod mount

138 degrees Wide field of view with no video distortion

Quiet & smooth mechanism movement, accurate & fast focus

Support Visca, Pelco-P&Pelco-D protocol, RS232/RS485 Camera Control

Compatible with most leading video conferencing software and platform

Compatible with all popular applications and cloud systems:



More Details



ACCURATE, SMOOTH AND SIENT PTZ MOVEMENT

Along with 340 degree pan & 120 degree tilt rotation at adjustable speed and fast & accurate focus to capture any view in conferencing space.



As EASY AS PLUG AND PLAY

Video output: USB2.0 Plug and play, Anyone can easily setup this USB Camera and control conferencing/ Live Streaming.

SUPERIOR QUALITY FULL GLASS LENS

with an Ultra-HD imaging system, Rally delivers brilliantly sharp video, and exceptional optical accuracy at esolutions up to 4K. This camera adopts 1/2.5"CMOS(SONY IMX274) 8.29 effective mage pixel



FIXED FACUS PAN TILE 138° FOV

Fiexed facus pan tile camera, 138 °wide field of view with no video distortion



MULTIPLE INSTALLATIONS



Support multiple mount way: available to install on desk, monitor, wall, tripod or up-side down in-ceiling.



COMPATIBLE WITH MAC® AND PC

Simply connect a PC or Mac®to conduct a meetings within the user's own familiar computing environment. Compatible with Mac and PC. System Requirements: Windows 7, 8.1 or 10,Mac OS X 10.7 or higher, Andriod, Linux.

Product Specifications

Model No	TEVO-VHD4K
Image Sensor	1/2.5" CMOS (SONY IMX274)
Effective pixel	8.29 mega pixel (16: 9)
Horizontal Resolution	4K(3840 x 2160), 2K(2560*1440), 1080P(1920*1080)
Lens	Fixed focus 2.1mm wide angle lens
Signal standard	NTSC/PAL
SNR ratio	≥48dB
Field of View	Fixed focus, Diagonal : 138 °, Horizontal: 120 °, Vertical: 100 °
Control terminal	RS-232, RS485
Pan movement range	340°(Max Speed 80°/S)
Tilt movement range	120°(Max Speed 60°/S)
Preset position	Remote-controller supports 9 presets, PELCO Control Protocol supports 255 presets
Control Protocol	VISCA, PELCO-D, PELCO-P (RS-232, RS485)

HD Video output	USB plug and play
Work Temperature	-10°~50°
Work Humidity	-20°~60°
Baud rate	2400/4800/9600/19200bps
Decoder	Built-in
Address Set	1~255
Installation	Support desktop, Tripod, Wall mount and Ceiling mount
Power supply	DC12V/2A
Power	12W
Weight	1.46kg/2.8kg(before / after packing)
Size	260*175*180 mm /296*225*218mm (before / after packing)
Accessories	DC 12V Power adaptor, IR remote control, Ceiling brackets & screws, Manual, RS-232C cable, USB cable

Connection

Include Ceiling Mount



Tenveo
makes any meeting better and easier

Headquarter
Web:www.tenveo.com
Address: Room 719-720, Block B,
Tianhui building, No.106, Yousong Rd,
Longhua District, Shenzhen, China
Tel: 86-755-8526-1373/8525-8499
Hotline: 400-1080-686
Email: sales01@tenveo.com

Hong Kong Branch
Address: 10F/F1003, Witthy commercial
building, 1A-1L, Kowloon, Mongkok, Tung
Choi Street, Hong Kong
Contacts: Sherry Wu
Mob:+86 137 2344 2940
Email:sherry@tenveo.com

Xi'an Branch
Address: 2302 Block A, Zhongdeng Wenjing Building,
Seoul Street, Weiyang District, Xi'an, Shaan'xi Province, China
Contact: Mr Tong
Tel:+86 187 1055 9198
Email:sales06@tenveo.com